

WHEEL LOADERS

Group
W8

Operating weight
22 - 25T

WHEEL LOADERS

Group
W8

Operating weight
22 - 25T

STANDARD BUCKETS

Description: standard bucket with rear bar or screwed skids; ESCO/CAT J tooth system; direct fit on pins or a quick coupler; blades HB500; side bar HB400; bottom stripes HB400;

CODE	Width [mm]	Capacity SAE [L]	Option	Dedicated to
WGP-W8-3800L	3000	3800	LW/Z*	Volvo, parallel kinematics
WGP-W8-4300L	3000	4300	LW/Z*	Volvo, parallel kinematics
WGP-W8-4600L	3200	4600	LW/Z*	Volvo, parallel kinematics
WGP-W8-5000L	3200	5000	LW/Z*	Volvo, parallel kinematics
WGP-W8-5500L	3400	5500	LW/Z*	Volvo, parallel kinematics
WGP-W8-4500L	3200	4500	LW/Z*	Cat, kinematics type Z
WGP-W8-4800L	3200	4800	LW/Z*	Cat, kinematics type Z
WGP-W8-5000L	3200	5000	LW/Z*	Cat, kinematics type Z

*LW/Z - optional interchangeable blade / teeth




BUCKETS WITH INCREASED CAPACITY

Description: light material bucket max. 600kg/m³; blade HB500; bottom stripes HB400; side bar HB400; direct fit on pins or a quick coupler

CODE	Width [mm]	Capacity SAE [L]	Option
WLM-W8-6000L	3200	6000	LW*
WLM-W8-7000L	3400	7000	LW*
WLM-W8-10000L	3700	10000	LW*
WLM-W8-12000L	3700	12000	LW*

*LW - optional interchangeable blade



ROCK BUCKETS

Description: rock bucket with screwed skids, grate to prevent scattering, ESCO/CAT J tooth system; direct fit on pins or a quick coupler; blades HB500; side bar HB400; bottom stripes HB400; body HB400; sides HB400

CODE	Width [mm]	Capacity SAE [L]	Option	Dedicated to
WHD-W8-3600L	3200	3600	Z, S*	Volvo, parallel kinematics
WHD-W8-4100L	3200	4100	Z, S*	Volvo, parallel kinematics
WHD-W8-3400L	3200	3400	Z, S*	Cat, kinematics type Z
WHD-W8-3600L	3200	3600	Z, S*	Cat, kinematics type Z
WHD-W8-4000L	3200	4000	Z, S*	Cat, kinematics type Z

*Z/S – teeth, segments




DEKPOL STEEL

HIGH DUMP BUCKETS

Description: bucket with cylinders placed from outside; blade HB500; bottom stripes HB400; side bar HB400; direct fit on pins or a quick coupler; *spoil density max. 600kg/m³

CODE	Width [mm]	Capacity SAE [L]	Option	Type
WHT-W8-6000L	3200	6000	LW*	Standard bucket
WHT-W8-7000L	3400	7000	LW*	Standard bucket
WHT-W8-11000L	3700	11000	LW*	Light material bucket*
WHT-W8-13000L	4000	13000	LW*	Light material bucket*

*LW - optional interchangeable blade



SKELETON BUCKETS

Description: bars spacing can be adjusted; blade HB500; side bar HB400; direct fit on pins or a quick coupler; ESCO/CAT J tooth system

CODE	Width [mm]	Capacity SAE [L]	Option
WS-W8-3500L	3200	3500	LW/Z*
WS-W8-4000L	3200	4000	LW/Z*
WS-W8-4500L	3200	4500	LW/Z*

*LW/Z - optional interchangeable blade / teeth



FORKS

Description: fork carrier standard FEM4A; direct fit on pins or a quick coupler

CODE	Lifting capacity per pair	Forks	Carrier width
WMF-W8-10000KG	10000kg	150x70x1600	1500



LOADER QUICK COUPLERS

Description: quick coupler to meet the standards from Volvo, Komatsu, CAT, JCB, Liebherr and others; hydraulic locking system

CODE	Quick coupler type	Version
WQC-W8-BBM	TYPE VOLVO BBM	Hydraulic



DEKPOL STEEL